

DECLARATION DE PERFORMANCE

AL-011

1. Unique identification code of the product type: „Adera Liss”
2. **Intended use:** Gypsum plaster for construction, C7 / 20/2, used for plastering and interior finishing. The recommended application thickness is minimum 1 mm, maximum 1 mm. Apply manually at a temperature of minimum 5 ° C, max. 35 ° C.
3. **Manufacturer:** ETEX BUILDING PERFORMANCE SA 98 Vulturilor Str., 5th floor, 030857, District 3, Bucharest, Romania, Phone: (+40) 31 224 01 00, Fax: (+40) 31 224 01 01 .
4. **The Performance Assessment and Verification System:** SYSTEM 4
5. **Harmonized standard:** SR EN 13279-1: 2009 “Gypsum binders and gypsum plasters”
6. **Declared performance:**

| Essential characteristics | Declared performance: | Harmonized technical specification |
|-----------------------------|-----------------------|------------------------------------|
| Fire reaction | Class A1 | EN 13279-1:2009 |
| Direct air sound insulation | PND | |
| Thermal resistance | PND | |

The Declaration of Performance, Technical Data Sheet and Safety Data Sheet are available at www.siniat.ro, and the instructions for use are found on the bag.

This declaration of performance is issued in accordance with EU Regulation no. 305/2011 and EU delegated Regulation no. 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Quality Manager
Oana Bindiu



Plant Manager
Cristian Moldovan



Aghiresu Fabrici 17.05.2022

